

BOX

X4-OB

X6-OB

specifications

PIXEL PITCH	4.8mm	6mm
VIRTUAL/REAL	real	real
LED TYPE	3-in-1 SMD	3-in-1 SMD
BRIGHTNESS IN NITS (CD/M2)	5500 (Calib)	5500 (Calib)
VIEWING ANGLE H/V	140/120	140/120
PIXEL DENSITY M2	43403	27778
PIXEL DENSITY SQ.FT.	4016	2570
PANEL SIZE(WXHXD) MM	1152x1728x345	1152x1728x345
PANEL SIZE(WXHXD) INCH	45.35x68.03x13.58	45.35x68.03x13.58
PANEL SURFACE IN M2	2.05	2.05
PANEL RESOLUTION (WXH)	240x360	192x288
INPUT VOLTAGE	110/220V ±10% (50/60Hz)	110/220V ±10% (50/60Hz)
PROCESSING DEPTH	20bit	20bit
COLORS	1153 quadrillions	1153 quadrillions
OPERATING TEMPERATURE	-30~-50°C/-22~-122°F	-30~-50°C/-22~-122°F
OPERATING HUMIDITY	10-90%RH	10-90%RH
ENVIRONMENT	IP65 (OUTDOOR)	IP65 (OUTDOOR)
LIFETIME AVG	100000	100000
CERTIFICATION(S)	ETL	ETL

**specifications subject to change, please inquire for current specs.*



VISIT OUR LED LAB:
475 Greenwich St.
New York, New York 10013

